

(ERP) ESWAR RUBBER PRODUCTS PVT LTD.,

AN ISO 9001: 2015 CERTIFIED COMPANY

Admin Office: Surya Towers, 12, Maravaneri Extension 2nd Cross, Salem - 636007, India. Contact: Ph: +91-427-4047677, 2452271. Email:info@rubberredaim.com. Web:www.rubberredaim.com

Rev.No:01 / 05.01.2017

PRODUCT DATA SHEET

Product Name High Tensile Reclaimed Rubber

Grade HTR - 704

Black slab rubber Sheets Appearance

STANDARD SPECIFICATION

S.NO	PROPERTIES	UNITS	LIMITS	TEST METHOD
CHEMICAL PROPERTIES				
1	ACETONE EXTRACT	%	14+/-3	IS 6306-1971
2	ASH CONTENT	%	7+/-2	IS 6306-1971
3	CARBON BLACK	%	26+/-3	IS 6306-1971
4	RUBBER HYDROCARBON	%	Min 47	IS 6306-1971
5	VOLATILE MATTER	%	< 1	IS 6306-1971
PHYSICAL PROPERTIES				
6	SPECIFIC GRAVITY		Max 1.15	IS 6306-1971
7	TENSILE STRENGTH	KG/SQ.CM	Min 70	IS 3400-1987
8	ELONGATION AT BREAK	%	Min 250	IS 3400-1987
9	HARDNESS	SHORE 'A'	60+/-5	IS 3400-1980
10	MOONEY VISCOSITY ML (1+4) @ 100°C	MU	4060	IS 6306-1971

Test Recipe: (Parts by Mass): Reclaim - 200, Zinc Oxide -5.0, Sulphur-3.0, Stearic Acid-2.0, MBT-0.5, DPG-0.2, Cure : slab - 145°C / 30 min

REACH (EU) Compliance: Our products are registered under REACH EU Regulation (EC) No:1907/2006 (REACH)

Highly refined reclaimed rubber derived from NR based Truck and Bus Tyres by the application of **Description:**

heat and chemical agents, followed by intense mechanical process.

Packing Option: HDPE Sacks - 25Kgs & 50Kgs, LDPE Bag - 25Kgs, EVA packing - 20Kgs & 10Kgs,

Pallet packing - 1MT.

Detailed advice on the Health safety aspects of this product is given in the individual product Health & Safety:

Material safety Datasheet (MSDS), available upon request.



